

Sociobiology An international journal on social insects

### Research article - Termites

# Utility of Acoustical Detection of Coptotermes formosanus (Isoptera: Rhinotermitidae)

### W. OSBRINK,<sup>1</sup> M. CORNELIUS<sup>2</sup>

1 - USDA-ARS-SPA, Kerrville, Texas, USA.

2 - USDA-ARS-BARC, Beltsville, Maryland, USA.

# Article History

Edited by:

Evandro N. Silva, UEFS - Brazil Received 29 November 2012 Initial acceptance 02 January 2013 Final acceptance 14 February 2013

#### Keywords

AED 2000, AED 2010, Formosan subterranean termite, tree, monitoring, pest control

#### Corresponding author

Weste Osbrink USDA-ARS-SPA Knipling-Bushland U.S. Livestock Insects Research Lab 2700 Fredericksburg Road, Kerrville, Texas 78028 - Phone: 504.330.41326 E-Mail: weste.osbrink@ars.usda.gov

### Introduction

#### Abstract

The AED 2000 and 2010 are extremely sensitive listening devices which can effectively detect and monitor termite activity through a wave guide (e.g. bolt) both qualitatively and quantitatively. Experiments conducted with one to ten thousand termites from differing colonies infesting wood in buckets demonstrated that acoustical emission detector readings significantly increased when number of termites increased. Termites were also detected in infested trees with the installation of several wave guides into their trunks. These devices can detect termites and changes in termite activity caused by changes in termite numbers, making it an effective pest management professional and research tool for finding and evaluating termite infestations and efficacy of treatments in specific locations.

Total economic loss due to termites in the United States has been estimated at \$11 billion per year, and where they occur, the Formosan termite, *Coptotermes formosanus* Shiraki (FST), is the most devastating termite pest in the world (Su, 2002). The FST was introduced into the United States from Asia when troops and equipment returned from World War II (Su & Tamashiro, 1987). In addition to structural infestations, *C. formosanus* infestations of living trees are common (Osbrink et al., 1999; Osbrink & Lax, 2002; Ring et al., 2002; Osbrink & Lax, 2003).

Development of techniques for detecting hidden termite infestations have produced only a few successful alternatives to traditional visual inspection methods (Lewis, 1997). Efficient non-invasive detection of termite activity can provide timely location of an infestation thereby reducing economic impact. Non-invasive detection is also ideal for evaluating the efficacy of control efforts because noninvasive monitoring has no effect on population dynamics. Conversely, invasive monitoring techniques can drive termites away from the monitor, creating an artifact of apparent control because of relocation of the termites (Aluko & Husseneder, 2007). Alternatives to visual inspection include monitoring devices with sensors that detect acoustic emissions of termites in wood (Fujii et al., 1990; Lewis & Lemaster, 1991; Noguchi et al., 1991; Robbins et al., 1991). Acoustic emission sensors are successful because they are nondestructive and operate at high frequencies (ca. 40 kHz) where there is negligible background noise to interfere with detection and interpretation of insect sounds (Lewis & Lemaster, 1991; Robbins et al., 1991). Acoustic emission systems have been applied as research tools to estimate termite population levels (Fujii et al., 1990, Lewis & Lemaster, 1991; Scheffrahn et al., 1993; Osbrink et al., 2011). Acoustic emission systems are also ideal for detection of termites in trees (Osbrink et al., 1999; Kramer, 2001; Mankin et al., 2002; Osbrink et al., 2011).

Understanding the efficacy and dynamics of acoustical detection is critical to it being successfully integrated



into an effective pest management strategy. The central objective of this research was to determine the efficacy of using the AED 2000 acoustical emissions detector (Acoustical Emissions Consulting, Inc Fair Oaks, CA) to detect and quantify termite infestations. To meet this objective, studies were conducted to monitor *C. formosanus* through acoustical emission detection both in the laboratory and in trees outdoors. These studies provide evidence that AED significant potential for application in termite management efforts.

# **Materials and Methods**

### Acoustical Emission Detector (AED)

An AED 2000 acoustical emissions detector (Acoustical Emissions Consulting, Inc Fair Oaks, CA) was used to quantify termite activity. Lag bolt wave guides (76.2 or 150 x 9 mm) were screwed horizontally into pre-drilled pilot holes in wood substrates. Acoustical emissions were detected with a sensor probe (Model SP-1L with Model DMH-30 high force magnetic accessory attachment, Acoustic Emission Consulting, Inc). AED counts were acquired for 60 s with accompanying software, which converts termite sounds to counts per second and enters them into Excel (Microsoft, Redmond WA). Only the numbers of counts in the first 10 s of the 60 s recording were used to represent each unique individual recording. If the first 10 s of recording was contaminated with interference noise (elevated spiked counts), the first 10 s of recording following the cessation of interference noise were used to represent the unique individual recording. Comparisons also were made between the AED 2000 and the more recently manufactured AED 2010 (Acoustical Emissions Consulting, Inc Fair Oaks, CA).

#### Laboratory Bucket Tests

A vertically oriented section of spruce (Picea sp.) 38 x 89 mm (2x4 inch) dimensional lumber 17 cm in length was attached to the inner side of a lidded plastic buckets (3.791, 18.5 cm height x 20 cm diam.) with 2 horizontally applied drywall screws (high and low) and central lag bolt wave guide (76.2 x 9 mm). The head of the lag bolt was accessible from the outside of the lidded bucket (Fig. 1). The bucket was filled to within 4 cm of top with a moist ( $\approx 20\%$  water wt/wt) mixture of sand and vermiculite (50:50 by volume). Ten holes were created in the sand-vermiculite substrate with a 5 ml pipette to increase surface area and accelerate acclimatization of termites. Four buckets were prepared for each of 4 termite densities (0, 1,000, 5,000, and 10,000 termites per bucket), in which each density level represents 4 distinct colonies (A, B, C, and D), one colony per bucket. In laboratory bucket tests there were 4 replicates (bucket A, B, C, D), each replicate consisting of a 10 s recording from

a specific bucket. Termites were obtained from bucket trap monitors (Su & Scheffrahn, 1986) and termite numbers determined by weight. Soldier proportions were about 10%, unchanged from when collected.

#### Termite Density Response at 7 and 14 d.

Formosan termites were placed in buckets on day 0 (0 d) as described above. Buckets were held in the laboratory ( $\approx 26.7^{\circ}$  C). On 7 d and 14 d AED readings were taken from each bucket. In laboratory bucket tests there were 4 replicates (bucket A, B, C, D), each replicate consisting of a 10 s recording from a specific bucket.

### Termite Density Response at Three Temperatures

After completion of readings at 14 d for dose response at 1 temperature, buckets were placed in 3 incubators stabilized at 15, 20, and 25° C, respectively, and evaluated according to the schedule indicated in Table 1. After readings, buckets were rotated to a new temperature (incubator) and allowed 24 h to acclimate before acoustic readings were again taken. Incubators space limitations required the D samples to be split to fit the 12 buckets into three incubators. In laboratory bucket tests there were 4 replicates (bucket A, B, C, D), each replicate consisting of a 10 s recording from a specific bucket.

### Disturbance Test

AED recordings were taken before and after the application of three sharp strikes with a screwdriver to the high density laboratory buckets. In laboratory bucket tests there were 4 replicates (bucket A, B, C, D), each replicate consisting of a 10 s recording from a specific bucket.

### Field Test on Trees

Nine wave guides in the form of lag bolts (150 x 9 mm) were screwed horizontally into pre-drilled pilot holes in the trunk of test trees facing north, east, south, and west (Fig 1). Four wave guides were installed at ground level, four at 20 cm above ground level, and one into the east side of the trunk at a height of approximately 122 cm from the ground. Test trees consisted of four southern live oak trees (Quercus virginiana Philip Miller) with a diameter at breast height (dbh) of  $\approx$  90 cm, adjacent to Su-bucket-trap-monitors active with C. formosanus (Su & Scheffrahn 1986) located on the City Park campus of the Southern Regional Research Center, New Orleans, LA. In field tests on trees, only the numbers of counts in the first 10 s of the 60 s recording were used to represent each unique individual recording. If the first 10 s of recording was contaminated with interference noise (elevated spiked counts), the first 10 s of recording following the cessation of interference noise were used to represent the unique individual recording. In field tests on trees, ten consecutive counts (10 s) were used to calculate mean ( $\pm$  SE) counts per second to quantify termite activity associated with each unique AED tree bolt attachment.

### Comparison of AED 2000 with AED 2010.

Eight different recordings from trees were conducted with each model of acoustical emissions detector and results were compared between the AED 2000 and the AED 2010. In field tests on trees, only the numbers of counts in the first 10 s of the 60 s recording were used to represent each unique individual recording. If the first 10 s of recording was contaminated with interference noise (elevated spiked counts), the first 10 s of recording following the cessation of interference noise were used to represent the unique individual recording. In field tests on trees, ten consecutive counts (10 s) were used to calculate mean ( $\pm$  SE) counts per second to quantify termite activity associated with each unique AED tree bolt attachment.

### Data Analysis.

Ten consecutive count values (10 s) were used to represent termite activity associated with each unique AED attachment. In laboratory bucket tests there were 4 replicates (bucket A, B, C, D), each replicate consisting of a 10 s recording from a specific bucket. In field tests on trees, ten consecutive counts (10 s) were used to calculate mean ( $\pm$ SE) counts per second to quantify termite activity associated with each unique AED tree bolt attachment. Acoustical data were analyzed using one way analysis of variance (ANOVA) with means separated using the protected Tukey test, P < 0.05 (Systat, 2008).

### Results

#### Termite Density Response at 7 and 14 d.

Buckets with no termites produced AED readings of zero (control). There were highly significant differences in termite activity between termite colonies, and acoustical emission activity increased concomitantly with increased termite density (Table 2). The highest density always had significantly greater activity than the lowest. Overall, there was no consistent change in termite acuity between 7 d and 14 d, however at the lowest density there was non-significant but numerically consistent increase in activity (Table 2).

### Termite Density Response at Three Temperatures.

Buckets with no termites produced AED readings of zero (control). At low termite density, there was no signifi-

Table 1. Incubator temperature and rotation of termite densities.

		Temp (° C)						
Colony	# Termites	10	15	20	25			
А	0 1000 5000 10000	Day1	Day 2	Day 3				
В	0 1000 5000 10000	Day 3	Day 1	Day 2				
С	0 1000 5000 10000	Day 2	Day 3	Day 1				
D	0 1000	Day 1	Day 2	Day 3				
D	5000 10000	Day 3	Day1	Day 2				

cant difference in inter-colony activity at all 3 temp (Table 3), but there was a significant increase in termite activity at the highest density with two colonies and combined colonies (Table 4). At 20 and 25° C there was always a significant activity dose response except with colony D which did not statistically but did numerically separate 5k from 10k (Table 3). Combined colonies demonstrated highly significant density dose response at all temps. At the highest density there was always significantly less termite activity at the lowest temp (Table 4). At lower density this temperature separation was not as clearly defined.

#### Disturbance Test

Three of the four colonies displayed a significant decrease in termite activity, and one colony had a numerical but non-significant increase in recorded activity (Table 5). Qualitatively, termite activity could be heard though the earphones to increase for a brief time before the recording began.

### Field Test on Trees

Out of the nine bolts per tree, generally only one or two had significantly high termite activity, with the remainder of the bolts displaying low termite activity (Table 6).

#### Comparison of AED 2000 with AED 2010

Of eight different recordings of trees, there was little difference observed between the AED 2000 and AED 2010. The AED 2010 had consistently higher readings that may indicate that it may be slightly more sensitive (Table 7).

### Discussion

### Termite Density Response at 7 and 14 d.

Having highly significant differences in termite activity between colonies is consistent with the generally accepted understanding that there can be profound inter-colony differences. These findings support the suggestion of Su and La Fage (1984) to use multiple colonies when conducting bioassays. A possible explanation of the non-significant but numerically consistent increase in activity at the lowest density is that it takes longer for fewer termites to create a gallery system in the wood. Increased size of galleries increases the surface area occupied by termites creating an opportunity for increased generation of acoustical emission.

# Termite Density Response at Three Temperatures.

Dose responses to density and temperature were demonstrated most clearly with the combined colony data due to the increased number of samples. These results demonstrate the efficacy of using an acoustical emission detector to detect and monitor termite activity. Because there were significant differences in the AED readings based on termite density, the detector can be useful not only in detecting the presence of termites but also in estimating population density in infested trees or structures.

### Disturbance Test.

Though a post-disturbance decrease in activity occurred, a substantial amount of termite activity remained (Table 5). Qualitatively, earphone monitoring indicated an immediate, brief increase in termite sounds in all instances that is consistent with absconding. Unpublished video has shown FST to cease feeding and abscond following a disturbance, and soldiers (incapable of chewing wood) produce characteristic termite sounds monitored with the AED 2000 (WO personal observation). Additionally, the presence of red imported fire ant colonies, Solenopsis invicta Buren, at tree study sites have produced sounds similar to termites (WO personal observation). Thus, results indicate that AED 2000 recordings are created by termite movement and not feeding activity, possibly a result tarsal claw-substrate interaction. This is inconsistent with reports of Scheffrahn et al. (1993) and Fujii et al. (1990) who attribute signals detected by their devices specifically to termite feeding. This difference in interpretation of results may reflect differences in the nature of the disturbance or in the specifics of the detection mechanism.

### Field Test on Trees.

Of the nine bolts per tree, generally only one or two transmitted high termite activity while the remainder of the bolts displayed low termite activity (Table 6). Energy attenuates much more rapidly horizontally across the trunk than vertically up and down the trunk (Mankin et al., 2002), suggesting that termite activity is oriented vertical to the bolt. Thus, a single bolt, or readings from a single point cannot determine that a tree is not infested with termites.

#### Limitations of AED 2000 and AED 2010.

Certain events can interfere with successful recording of termite activity including wind noise, trucks with squeaking breaks, generators, crowd noise, etc. Wind speeds > 14 km/h interfere with recording activity in trees because of leaf flutter, and Excel recordings do not distinguish termite events from unrelated sound events, therefore maintaining a log with qualitative notes is advised. Elevated wind can be a common cause for cancellation of field tests, and demands flexibility in scheduling. Radio interference can also become an issue that may be mitigated by incorporating ferrite chokes and the shortest cord possible.

In conclusion, the AED 2000 and 2010 are extremely sensitive devises which can detect termite activity channeled through a wave guide. Because of the significant increases in AED readings with increasing group size, a trained pest management professional would be able to use the acoustical detectors to estimate the severity of an infestation, in addition to merely determining the presence or absence of termites. Use of this technology may be quite valuable in specific applications such as pre- and post-treatment evaluations of termite activity. In applications where multiple locations are to be evaluated, interference from external noise can become an issue.

#### Acknowledgements

We thank R. Davey, K. Lohmeyer, J.M. Pound, and S. Skoda for agreeing to review this manuscript and valuable improvements contributed by their reviews.

#### References

Aluko, G. & Husseneder, C. (2007) Colony dynamics of the Formosan subterranean termite in a frequently disturbed urban landscape. J. Econ. Entomol., 100: 1037-1046. doi: 10.1603/0022-0493(2007)100[1037:CDOTFS]2.0.CO;2

Fujii, Y., Noguchi, M., Imamura, Y. & Tokoro, M. (1990) Using acoustic emission monitoring to detect termite activity in wood. For. Prod. J., 40: 34-36.

Kramer, R. (2001) Detector for termites in soil? Pest Control Tech., 29: 130-131.

Lewis, V. R. (1997) Alternative control strategies for termites. J. Agric. Entomol., 14: 291-307.



Figure 1. AED 2000 attached to bucket and tree.

Lewis, V. R. & Lemaster, R. (1991) The potential of using acoustical emission to detect termites within wood. In: M. I. Haverty & W. W. Wilcox (Eds.), Proceedings of the symposium on current research on wood-destroying organisms and future prospects for protecting wood in use (pp. 34-37). Washington, DC: USDA For. Serv. Gen. Tech. Rep. PSW-128.

Mankin, R. W., Osbrink, W, Oi, F. & Anderson, J. (2002) Acoustic detection of termite infestations in urban trees. J. Econ. Entomol., 95: 981-988. doi: 10.1603/0022-0493-95.5.981

Noguchi, M., Fujii, Y., Owada, M., Imamura, Y., Tokoro, M. & Tooya, R. (1991) AE monitoring to detect termite attack on wood of commercial dimension and posts. For. Prod. J., 41: 32-36.

Osbrink, W. & Lax, A. (2002) Termite (Isoptera) gallery characterization in living trees using digital resistograph technology. In: W. C. Jones, J. Zhai, & W. H. Robinson (Eds.), Proceedings, 4th International Conference on Urban Pests (pp. 251-257). Charleston, SC, USA. Pocahontas Press, Inc. Blacksburg, Virginia, U.S.A.

Osbrink, W. & Lax, A. R. (2003) Effect of imidacloprid tree treatments on the occurrence of Formosan subterranean termites, Coptotermes formosanus Shiraki (Isoptera: Rhinotermitidae). J. Econ. Entomol., 96: 117-125. doi: 10.1603/0022-0493-96.1.117

Osbrink, W., Woodson, W. & Lax, A. R. (1999) Population of Formosan subterranean termite, *Coptotermes formosanus* (Isoptera: Rhinotermitidae), established in living urban trees in New Orleans, Louisiana, U. S. A., pp. 341-345. In: W. H. Robinson, F. Rettich, & G. W. Rambo (Eds.), Proceedings, 3rd International Conference on Urban Pests (pp. 341-345). Prague, Czech Republic. Graficke zavody Hronov, Czech Republic.

Osbrink, W., Cornelius, M. & Lax, A. (2011) Area wide field study on effects of three chitin synthesis inhibitor baits on populations of *Coptotermes formosanus* and *Reticulitermes flavipes* (Isoptera: Rhinotermitidae). J. Econ. Entomol., 104: 1009-1017. doi: 10.1603/EC10217

Ring, D., Henderson, G. and McCown, C. (2002) Evaluation of the Louisiana state program to treat trees infested with Formosan subterranean termites (Isoptera: Rhinotermitidae) in Louisiana, pp. 259-266. In: S. C. Jones, J. Zhai, & W. H. Robertson (Eds.), Proceedings of the 4th International Congress on Urban Pests (PP. 259-266). Blacksburg, VA: Pocahontas Press.

Robbins, W. P., Mueller R., Schaal, T. & Ebeling, T. (1991) Characteristics of acoustic emission signals generated by termite activity in wood. In: Proceedings, IEEE Ultrasonics Symposium (pp. 1047-1051). Orlando, FL. Conference Publications.

Scheffrahn, R., Robbins, W., Busey, P., Su, N.-Y. & Mueller, R. (1993) Evaluation of a novel, had-held, acoustic emissions detector to monitor termites (Isoptera: Kalotermitidae, Rhinotermitidae) in wood. J. Econ. Entomol., 86: 1720-1729.

Su, N.-Y. (2002) Novel technologies for subterranean termite control. Sociobiology, 40: 95-101.

Su, N.-Y. & La Fage, J. (1984) Differences in survival and feeding activity among colonies of the Formosan subterranean termite (Isoptera: Rhinotermitidae). Z. Angew. Entomol., 94: 134-138.

Su, N.-Y. & Scheffrahn, R. (1986) A method to access, trap, and monitor field populations of the Formosan subterranean termite (Isoptera: Rhinotermitidae) in the urban environment. Sociobiology, 12: 299-304.

Su, N.-Y. & Tamashiro, M. (1987) An overview of the Formosan subterranean termite (Isoptera: Rhinotermitidae) in the world. In: M. Tamashiro & N.-Y. Su (Eds.), Biology and control of the Formosan subterranean termite. Hawaii Institute of Tropical Agriculture and Human Resources Research Extension Series 083 (pp. 3-15). Honolulu, HI: University of Hawaii and Manoa. Systat Software. (2008) SigmaPlot users guide: statistics, version 11. Systat Software, Inc. San Jose, CA.

		7 d	Number termites (x1	,000) 14	d	
Colony	1	5	10	1	5	10
А	$23.8 \pm 4.4 \text{cB}$	189.9 ±25.5 aA	$235.6 \pm 12.3$ aB	$65.8 \pm 1.3$ cA F = 34.703	$105.0 \pm 8.9 \text{bC}$ df = 5, 59	$129.5 \pm 12.4$ bB P < 0.001
В	$13.3 \pm 2.7$ cBC	$96.0 \pm 11.9 \text{bB}$	$146.8 \pm 29.9 bC$	$24.0 \pm 3.0$ cB F = 26.757	$152.7 \pm 14.2abA$ df = 5, 59	$210.8 \pm 14.7 aC$ P < 0.001
С	$6.5 \pm 1.9 dC$	$39.1 \pm 7.4 cdB$	$124.0 \pm 16.2 bC$	$19.7 \pm 2.6$ dB F = 40.423	$56.9 \pm 7.3$ cB df = 5, 59	$176.0 \pm 16.4 aBC$ P < 0.001
D	$46.4 \pm 4.1 dA$	$166.0 \pm 9.5$ cA	$744.3 \pm 23.4aA$	$60.7 \pm 6.7$ dA F = 229.179	$149.7 \pm 16.0$ cAC df = 5, 59	$320.2 \pm 29.1$ bA P < 0.001
	F=25.790 df=3.39 P<0.001	F=20.158 df=3.39 P<0.001	F=195.680 df=3.39 P<0.001	F=36.223 df=3.39 P<0.001	F=13.753 df=3.39 P<0.001	F=17.787 df=3.39 P<0.001

## **Table 2**. Acoustical emission dose response (mean $\pm$ SE) by termites (10 s).

Means within a row (lower case) or column (upper case.) with same letter are not significantly different, protected Tukey Test (P > 0.05).

Table 3	. Varied	l temperature with	I AED	dose response	e (mean ± SE	) b	y termites (	(10 s	)
---------	----------	--------------------	-------	---------------	--------------	-----	--------------	-------	---

				Colony					
Temp	. # Termit	es							
(° C)	(x1,000)	А	В	С	D	Combined			
15	1000	$1.5\pm0.5aB$	$3.2\pm0.7aB$	$2.9\pm0.8aB$	$2.9\pm0.9aB$	$2.6 \pm 0.4 aC$	F = 0.808	df = 4, 79	P = 0.524
	5000	$17.4 \pm 2.8abAC$	$28.0\pm4.6aAC$	$2.7\pm0.6cB$	$10.4 \pm 2.7 bcB$	$14.6 \pm 2.1 \text{bB}$	F = 6.463	df = 4, 79	P < 0.001
	10000	$15.5 \pm 3.4 bC$	$18.4 \pm 2.3 bC$	$34.3\pm 6.0 abA$	$57.3 \pm 6.0 aA$	$31.3 \pm 3.5 bA$	F = 7.678	df = 4, 79	P < 0.001
		F = 11.7	F = 17.418	F = 26.681	F = 59.908	F = 37.647			
		df = 2, 29	df = 2, 29	df = 2, 29	df = 2, 29	df = 2, 119			
		P < 0.001	P < 0.001	P < 0.001	P < 0.001	P < 0.001			
20	1000	$3.0 \pm 1.2aC$	$2.1\pm0.7aC$	$1.1 \pm 0.4aC$	$2.2\pm0.4aB$	$2.1 \pm 0.4 aC$	F = 0.767	df = 4, 79	P = 0.550
	5000	$25.2 \pm 6.1 abB$	$28.1\pm5.1abB$	$23.9\pm4.1bB$	$51.1\pm9.4aA$	$32.1\pm3.6abB$	F = 2.623	df = 4, 79	P = 0.041
	10000	$45.3\pm5.4aA$	$57.8 \pm 6.2 aA$	$54.1\pm4.9aA$	$63.9 \pm 7.6 aA$	$55.3 \pm 3.1 aA$	F = 1.204	df = 4, 79	P = 0.316
		F = 19.643	F = 36.039	F = 57.422	F = 21.872	F = 93.620			
		df=2.29	df=2.29	df=2.29	df=2.29	df=2.29			
		P < 0.001	P < 0.001	P < 0.001	P < 0.001	P < 0.001			
25	1000	$17.0 \pm 5.2 aC$	$2.4\pm0.6aC$	$14.1 \pm 3.9aC$	$5.8 \pm 1.7 aC$	$13.5 \pm 2.2aC$	F = 2.751	df = 4, 79	P = 0.034
	5000	$53.4\pm4.6aB$	$42.7\pm5.6abB$	$30.9\pm4.3bB$	$32.3\pm4.5b\mathrm{B}$	$42.5 \pm 2.8 abB$	F = 3.195	df = 4, 79	P = 0.018
	10000	$159.3 \pm 12.9 aA$	$65.9\pm6.2 bcA$	$69.7 \pm 4.9 bcA$	$46.3 \pm 3.3$ cA	$108.7\pm9.4 bA$	F = 10.226	df = 4, 79	P < 0.001
		F = 76.815	F = 44.548	F = 42.584	F = 37.628	F = 70.673			
		df = 2, 29	df = 2, 29	df = 2, 29	df = 2, 29	df = 2, 29			
		P < 0.001	P < 0.001	P < 0.001	P < 0.001	P < 0.001			

Means within a row (lower case) or column (upper case) with same letter are not significantly different, protected Tukey Test (P > 0.05).

Temp.	Number termites		Colony				
(° C)	(x1,000)	А	В	С	D	Combined	
15	10	$15.5 \pm 3.3c$	$18.4 \pm 2.3b$	$34.3\pm6.0b$	$57.3 \pm 6.0a$	$31.4 \pm 3.5c$	
20	10	$45.3\pm5.4b$	$57.8 \pm 6.2a$	$57.8 \pm 5.1a$	$63.9 \pm 7.6a$	$55.3 \pm 3.1b$	
25	10	$159.3 \pm 12.9a$	$65.9\pm6.2a$	$69.7\pm4.9a$	$46.3 \pm 3.3a$	$108.7 \pm 9.4a$	
		F = 83.805	<i>F</i> = 23.678	F = 26.681	F = 2.290	<i>F</i> = 42.547	
		df = 2, 29	df = 2, 29	df = 2, 29	df = 2, 29	df = 2, 119	
		P < 0.001	P < 0.001	P < 0.001	P = 0.121	P < 0.001	
15	5	$17.4 \pm 2.8a$	$28.0 \pm 4.6a$	$2.7\pm0.6b$	$10.4 \pm 2.7b$	$14.6 \pm 2.1c$	
20	5	$3.0 \pm 1.2b$	$28.1 \pm 5.1a$	$23.9\pm4.1a$	$51.1 \pm 9.4a$	32.1± 3.6b	
25	5	$17.0 \pm 5.2a$	$42.7 \pm 5.6a$	$30.9\pm4.3a$	$32.3\pm4.5a$	$42.5\pm2.8a$	
		<i>F</i> = 5.566	<i>F</i> = 2.754	F = 18.182	F = 10.796	<i>F</i> = 23.928	
		df = 2, 29	df = 2, 29	df = 2, 29	df = 2, 29	df = 2, 119	
		P = 0.009	P = 0.082	P < 0.001	P < 0.001	P < 0.001	
15	1	$1.5 \pm 0.5 b$	$3.2 \pm 0.7a$	$2.9\pm0.9b$	$2.9 \pm 0.9a$	$2.6\pm0.4b$	
20	1	$3.0 \pm 1.2 b$	$2.1\pm0.7a$	$1.1\pm0.4b$	$2.2 \pm 0.4a$	$2.1\pm0.4b$	
25	1	$17.0 \pm 5.2a$	$2.4 \pm 0.6a$	$14.1 \pm 3.9a$	$5.8 \pm 1.7a$	$13.5 \pm 2.2a$	
		F = 7.659	F = 0.699	F = 9.171	F = 2.859	<i>F</i> = 24.819	
		df = 2, 29	df = 2, 29	df = 2, 29	df = 2, 29	df = 2, 119	
		P = 0.002	P = 0.506	P < 0.001	P = 0.075	P < 0.001	

Table 4. Temperature and termite density; mean ( $\pm$  SE) number of AED counts (10 s).

Means within a row with same letter not significantly different, protected Tukey Test (P > 0.05).

Table 5. Pre - and post - disturbance mean ( $\pm$  SE) number AED counts (10 s) of termites.

Colony	Termite dist	urbance			
	Pre-	Post-			
Α	$126.0 \pm 9.5a$	222.8 ± 109.5a	F = 0.776	df = 1, 19	P = 0.390
В	$141.0 \pm 8.3a$	$70.6\pm10.5b$	F = 27.742	df = 1, 19	P < 0.001
С	$255.3 \pm 17.4a$	$180.8\pm27.9b$	F = 5.137	df = 1, 19	P = 0.036
D	$272.5 \pm 19.1a$	$91.4\pm18.9b$	F = 45.558	df = 1, 19	P < 0.001

Means within a row with same letter not significantly different, protected Tukey Test (P > 0.05).

	Wave guide location on tree								
Oak Trees	North			East		South		West	t
	Base	20 cm	Base	20 cm	122 cm	base	20 cm	base	20 cm
1	$3.0 \pm 0.1c$	$4.2 \pm 0.8c$	$2.8 \pm 0.5c$	$14.3 \pm 4.4bc$	$2.8 \pm 2.8c$	$23.5 \pm 5.7b$	2.1±0.4c	3.5±0.9c	58.2±5.2a
							F = 37.895	df = 8, 89	P < 0.001
2	$3.7\pm0.1b$	$3.2\pm0.1b$	$1.9 \pm 0.5b$	$2.4\pm0.6b$	$4.2\pm0.6b$	$3.2\pm0.7b$	354.6±55.4a	35.1±6.1b	4.1±1.3b
							F = 39.070	df = 8, 89	P < 0.001
3	276.0 ± 9.1a	$4.3 \pm 1.0 b$	$3.9 \pm 0.9 b$	$5.0\pm0.5b$	$5.0\pm0.7b$	$8.9\pm2.7b$	3.2±0.5b	4.3±0.9b	1.2±0.9b
							<i>F</i> = 777.511	df = 8, 89	P < 0.001
4	$25.6 \pm 4.1b$	$0.0\pm0.0b$	$3.9 \pm 0.6b$	149.7 ± 19.1a	$5.9 \pm 0.8 b$	$3.3\pm0.9b$	6.7±1.2b	0.0±0.0b	4.6±0.8b
							F = 54.887	df = 8, 89	<i>P</i> < 0.001

**Table 6**. AED counts (10 s) of termites in trees (mean  $\pm$  SE).

Means within a row with same letter not significantly different, protected Tukey Test (P > 0.05).

	Wave guide location on tree									
Oak	Trees	North	East	South	West					
6	AED 2010	2.6 ± 0.9a	8.9 ± 2.0a	17.9 ± 3.3a	3.5 ± 1.5a					
	AED 2000	$0.3 \pm 0.2b$	$1.9 \pm 0.8b$	$12.7 \pm 2.5b$	$0.9 \pm 0.6a$					
		F = 6.065	<i>F</i> = 10.357	<i>F</i> = 1.535	<i>F</i> = 2.500					
		df=1,19	df = 1, 19	df=1, 19	df = 1, 19					
		P = 0.024	P = 0.005	P = 0.231	P = 0.131					
				South (March)	South (June)					
350	AED 2010	1.9 ± 1.0a	$0.5 \pm 0.3a$	13.7 ± 3.6a	47.2± 6.0a					
	AED 2000	$0.9 \pm 0.4a$	$0.0 \pm 0.0a$	8.2 ± 1.3a	$27.2 \pm 2.3b$					
		F = 0.820	<i>F</i> = 2.143	F = 2.041	<i>F</i> = 9.571					
		df = 1, 19	df = 1, 19	df = 1, 19	df = 1, 19					
		<i>P</i> = 0.377	P = 0.160	P = 0.170	<i>P</i> = 0.006					

Table 7. Comparison of AED 2000 with AED 2010 with AED counts (10 s) of termites in trees (mean ± SE).

Means within a row with same letter not significantly different protected, Tukey Test (P > 0.05).